

12 Output Fuseless Slave PDU

eMU-FS

Description

The eMU-FS is a twelve output, fuseless power distribution unit that can be remotely controlled and monitored from an eMU-FM (LAN Enabled PDU)

Features:

- Inputs** 20A 'Powercon' connector with front panel 16A fuse.
- Outputs** Twelve IEC outputs.
- Status LED** Front panel LEDs show the status of each output.
ON – Output relay is on and the fuse is OK
OFF – Output relay has been switched off
- Sequential Switch On** On power up the outputs can be programmed to switch on sequentially to avoid switch on current surges.
- Power Shedding** Outputs can be setup as non critical, so in the event of needing to reduce the power load, these outputs can be 'shed' by a single closing contact input.
- Embedded Web Server** The status, control and setup can be accessed via standard web browsers (if it is connected to an LAN Enabled eMU-FM).
- LAN Control** A TCP socket protocol enables the eMU-S to be controlled by third user developed or third party software like Crestron or AMX (if it is connected to an LAN Enabled eMU-FM).
- Email Alerts** Ups on/off event notification via SMTP (if it is connected to an LAN Enabled eMU-FM).
- Options** Rear cable tiebar.
- Dimensions** 1U x 250mm deep.
- Weight** 3kg

Key Features

- 20A Powercon Input
- 16A Input Fuse
- 12 IEC Outputs
- Sequential Power On
- Power Shedding
- LAN Control via LAN Enabled eMU-FM
- 1U x 250mm Deep



**31 JESSOPS RIVERSIDE
SHEFFIELD
S9 2RX
ENGLAND
TEL +44 (0)114 242 2333
FAX +44 (0)114 243 3913
email info@audionics.co.uk
Web www.audionics.co.uk**

