

Logic to IP Converter

eXP16

Description

The eXP16 is a 1U, 19", rackmount unit with integral mains power supply. It enables monitoring of sixteen logic inputs and sixteen logic outputs over LAN/WAN.

Features:

Logic Inputs – 16 local logic inputs, which can be configured as closing contact, active high or active low.

The status of the logic inputs can be remotely monitored via the LAN/WAN, any changes of state of the inputs are broadcast to all connected clients.

Logic Outputs – 16 dry closing contacts, which can be remotely controlled via the LAN/WAN.

RS232 System Port – The eXP16 has an RS232 port which enables the user to configure the IP address and retrieve current status of unit and clients connected.

Front Panel Status LEDs – 32 front panel LEDs show the current status of logic inputs and outputs.

Additional Slave Units – Up to eight slave units can be connected via RS485 serial data. All can be controlled from the master unit LAN connection.

Remote Control:

Up to 8 clients can connect to the eXP16 by opening an IP socket. The clients are then able to interrogate the status of the logic inputs and the status of the logic outputs.

The logic outputs can be switched on, switched off or flashed with adjustable duration.

Connected clients are also notified of any changes to the input logic status.

The protocol is simple to enable users to develop their own software applications.

Applications

The eXP16 has been designed to enable software based systems to interface directly with existing logic control systems.

Key Features

16 Logic Inputs

16 Logic Outputs

Remote Control via LAN/WAN

Logic > IP Conversion

Simple Control Protocol

Control of 7 Slaves

8 way units available

RS232 control available



AUDIONICS
professional broadcast equipment

**31 JESSOPS RIVERSIDE
SHEFFIELD
S9 2RX
ENGLAND
TEL +44 (0)114 242 2333
FAX +44 (0)114 243 3913
email info@audionics.co.uk
Web www.audionics.co.uk**

