

## Audionics Power Distribution - Product Comparison Chart

Product Code	Description	No. Inputs	No. Outputs	Sequential Switch On	Power Shedding	Output Fuses	Embedded Web Server	Internet Control	Email Alerts	Auto Input Changeover	Temperature Sensors	Current Measurement	Dimensions	Weight
eMU-M	12 Output PDU - LAN Enabled	1	12	✓	✓	✓	✓	✓	✓				1U (44x483x250mm)	3kg
eMU-S	12 Output PDU	1	12	✓	✓	✓		Via Master	Via Master				1U (44x483x250mm)	3kg
eMU-FM	12 Output Fuseless PDU - LAN Enabled	1	12	✓	✓		✓	✓	✓				1U (44x483x250mm)	3kg
eMU-FS	12 Output Fuseless PDU	1	12	✓	✓			Via Master	Via Master				1U (44x483x250mm)	3kg
eMU-2M	12 Output PDU - LAN Enabled - Ver 2	1	12	✓	✓	✓	✓	✓	✓		✓	✓	1U (44x483x250mm)	3kg
eMU-2S	12 Output PDU - Ver 2	1	12	✓	✓	✓		Via Master	Via Master		✓	✓	1U (44x483x250mm)	3kg
eMU-ACO-M	10 Output Dual Input PDU - LAN Enabled	2	10	✓	✓	✓	✓	✓	✓	✓	✓	✓	1U (44x483x250mm)	3kg
eMU-ACO-S	10 Output Dual Input PDU	2	10	✓	✓	✓		Via Master	Via Master	✓	✓	✓	1U (44x483x250mm)	3kg
ACO-1	Dual Input Auto Changeover Unit	2	1							✓			1U (44x483x250mm)	3kg
ACO-MDU-12	12 Output Auto Changeover PDU	2	12			✓				✓			1U (44x483x250mm)	3kg
MDU-12	12 Output Standard PDU	1	12			✓							1U (44x483x150mm)	3kg
MDU-12T	12 Output Enhanced PDU	1	12			✓					✓	✓	1U (44x483x150mm)	3kg
MDU-TB	Rear Cable Tiebar												430mmx100mm	
MDU-TS	Temperature Sensor												1m length	